

## SPECTRA NEWPORT 1000c WATERMAKER

## PRODUCT SPECIFICATIONS

Production / Day 1000 gal (3785 l) Production / Hour 41 gal (155 l) Power Requirement

24v DC 28A 110v AC 10A 220v AC 5A

DC Systems 182 lbs (83 kg) AC Systems 177 lbs (80.3 kg) Weight

Pre Filters 2.5"x10" pleated polyester 5 micron 2.5"x10" pleated polyester 20 micron

Controls Spectra Connect Controller

Dedicated thruhull, dry and well ventilated area not to exceed 110F/37C Installation Requirements

Membranes (3) 40" x 2.5" High rejection spiral wound

polyamide

Pump and Motor Carbon vane pump with variable speed

commercial motor

99.2% Salt Rejection

Max 110F/37C Min 36F/2C Temperature Range

33,000 PPM feed water at 77F/25C **Baseline Conditions** 

3-11 (typical seawater pH is 8) pH Range

Chlorine Tolerance O PPM

Warranty Spectra standard warranty

Shipping Weight 200 lbs (91 kg)

Box 1 47"x23"x18" Box 2 32"x24"x24" Shipping Dimensions

Box 1 120cm x 59cm x 46cm Box 2 81cm x 61cm x 61cm



### **FACTS**

The Newport 1000c is available in DC and AC Voltages. Systems use motor speed control technology, allowing for quiet operation on an inverter or straight off the battery bank. Multi-speed capacity allows the machine to operate at its' optimum speed in all conditions. The system will automatically switch to low mode to extend the prefilter life in challenging feed water. The Spectra Connect allows you to operate and monitor your watermaker from a remote device, and has new added features like the Fill Tank mode, or a customizable Auto Run mode, One-Touch Sensor Calibration, and suggested maintenance intervals displayed on the dashboard.

## **FEATURES**

- Completely automated with the Spectra Connect Controller
- Compact modular design
- Spectra's unique Clark Pump for efficiency and reliability
- High and low speed operation for customizable power management and output volume
- Low power consumption, can be run on batteries, solar, or wind power
- Whisper quiet
- Commercial grade Magdrive pump with run dry protection Commercial grade, continuous duty motor
- Manual bypass for diversion valve
- System includes installation kit and product sample valve
- Also available with additional local display
- Z±ION Compatible



# SPECTRA NEWPORT 1000c WATERMAKER



Feed Pump Module Depth 13.5" / 34 cm





44" / 112 cm High Pressure Clark Pump and Membrane Depth 12" / 30.5 cm







Katadyn reserves the right to modify products

Katadyn Desalination LLC.

Spectra Watermakers 2220 S McDowell Blvd Ext Petaluma, CA 94954

TEL: 1-415-526-2780 FAX: 1-414-526-2787

E-MAIL: sales@spectrawatermakers.com

www.spectrawatermakers.com